



INT-FO-P2P-D/S

FIBER OPTIC INTERFACES

(FOR CHAMELEON NETWORK)

The INT-FO-P2P-D interface allows double peer-to-peer Fiber Optic connection, making possible to build a closed loop, “daisy-chained” communication network between GFE's CHAMELEON Panels (GEKKO, OCTO+, NODE+ and CHAMELEON REPEATER).

The INT-FO-P2P-S interface allows one single Fiber Optic connection. Mainly used for integration to 3rd party BMS systems or for a single extension connection to a CHAMELEON Display.

For more detailed information, such as commissioning, network topology 1 options and installation troubleshooting, please refer to the CHAMELEON Network manual or contact our Technical Support team.

KEY FEATURES

- Full electrical Isolation between connections
- Independent network paths
- Compatible only with GFE CHAMELEON Panels
- 2500m maximum cable length between interfaces

TECHNICAL SPECIFICATIONS

POWER SUPPLY RATING	24V DC (17V to 30V DC)
SUPPLY CURRENT	15 mA
RECOMMENDED CABLE / CONNECTOR	Multi-mode 62.5/125 µm with ST Connector
MAXIMUM CABLE DISTANCE	2500m per connection
OPERATING/ STORAGE TEMPERATURE	-10°C to 50°C
PROTECTION / HUMIDITY	IP30 / Max 85% RH Non-Condensing
WEIGHT / DIMENSIONS	33 g / 90 (L) x 40 (H) x 20 (W) mm
COMPATIBILITY	All CHAMELEON Panels (GEKKO, OCTO+, NODE+, CHAMELEON-REP)

ORDER CODE

INT-FO-P2P-D	FO DOUBLE (double channel for CHAMELEON CLOSED LOOP)
INT-FO-P2P-S	FO SINGLE (single channel used on BMS or CHAMELEON DISPLAY)