

## Eclipse LED 16A LED Keypad

## EN 50131 GRADE 2 Class II

### Description

LED 16A is a keypad with LED indication of zones, system troubles, alarm messages and arming type. It is part of the ECLIPSE series alarm systems. The keyboard provides 1 input zone. LED 16A is suitable for programming and management of systems with up to 3 independent areas and up to 16 zones.

### Technical Specifications

Power Supply from the control panel . . . .	9-18V (nom. 14V)
Consumption . . . . .	Min. 50mA / Max. 80mA
Area Indication . . . . .	3
Zone Indication . . . . .	16
Panic buttons . . . . .	Yes
Buttons . . . . .	Rubber
Operation temperature . . . . .	-20 to +50°C
Tamper . . . . .	Yes
Dimensions . . . . .	100x90x24mm



### Functional Specifications

- Shortcut buttons to additional menus – Memory, Troubles display and Bypassed zones;
- Quick buttons for all arming modes;
- 3 fast buttons' combination for sending of PANIC, MEDICAL and FIRE alarm messages to a central monitoring station;
- The system parameters can be fully programmed;
- Supports 2 programming types: 4-digit addresses and 3-digit operations;
- Adjustable intensity of backlight for the display and buttons;
- Adjustable sound volume of the internal buzzer.

### Packing Information

- **Master box** - 80 units LED 16A, dimensions 496 x 305 x 206 mm

### Compatible Product Range

- **Eclipse Series** - Alarm Control Panels
- **AUMS-12S** - magnetic contacts

### Contact Information