



VALKYRIE AS

ADDRESSABLE WALL MOUNT SOUNDER/ BEACON





The VALKYRIE AS is a Wall Mounted Addressable Sounder/ Beacon with low power consumption. Up to 32 individually addressed sounders can be installed per loop occupying address 94 to 125. The address is set using switches 1 to 5 of the 8 way DIL switch. Four different tones are available and selected using DIL switches 6 and 7.

When individual address reporting is not required, VALKYRIE AS can be configured as a Shadow Sounder. In this case sounders do not occupy an address in the loop thus freeing up addresses for more detection devices. Shadow sounders do not report back to the control panel so their presence on the loop is not monitored. Shadow sounders draw current from the loop (10 mA in alarm) and must be included in loop load calculations.

TECHNICAL SPECIFICATIONS		
SUPPLY VOLTAGE	Loop Powered - 20V to 30V DC	
LOOP CURRENT - QUIESCENT	550 uA max. with isolator	
LOOP CURRENT - SOUNDER/BEACON ACTIVE	10 mA - 280 mW @ 28V DC included isolator	
MAXIMUM SOUNDER OUTPUT	100 dB (@ 1 meter - 30V DC)	
LIGHT FLASH RATE	0,92 Hz	
CABLE SIZE	0.5-2.5 mm²	
RESET/START-UP TIMES	20 seconds max.	
PROTECTION CATEGORY	Type A - Indoor Use / Rating IP21C	
COLOUR / CASE MATERIAL	Red or White / ABS and PC	
OPERATION TEMPERATURE	-10°C to 55°C	
MAX. HUMIDITY	95% RH Non-Condensing	
DIMENSIONS	110 (D) x 85 (H) mm included base	
WEIGHT	254g inc. base & 304g inc. packaging	
For EN54-13 compliance, please check the control panel manual specifications.		











ORDER CODE		
VALKYRIE AS	ADDRESSABLE WALL SOUNDER	1328-CPR-0286 0359-UKCA-CPR-00193
VALKYRIE ASB	ADDRESSABLE WALL SOUNDER/ BEACON	1328-CPR-0286 0359-UKCA-CPR-00193
VALKYRIE ASI	ADDRESSABLE WALL SOUNDER WITH ISOLATOR	1328-CPR-0286 0359-UKCA-CPR-00193
VALKYRIE ASBI	ADDRESSABLE WALL SOUNDER/ BEACON WITH ISOLATOR	1328-CPR-0286 0359-UKCA-CPR-00193





