



## VALKYRIE AS IP65

**Addressable Wall Mount  
Sounder/ Beacon  
Outdoor Use-IP65**



1328-CPR-0299  
CERTIFIED

The VALKYRIE AS IP65 is a Wall Mounted Addressable Sounder/ Beacon with low power consumption. It is specifically designed to be used outdoors. Up to 32 individually addressed sounders can be installed per loop occupying address 94 to 125. The address is set using switches 1 to 5 of the 8 way DIL switch. Four different tones are available and selected using DIL switches 6 and 7.

When individual address reporting is not required, VALKYRIE AS IP65 can be configured as a Shadow Sounder. In this case sounders do not occupy an address in the loop thus freeing up addresses for more detection devices. Shadow sounders do not report back to the control panel so their presence on the loop is not monitored. Shadow sounders draw current from the loop (10 mA in alarm) and must be included in loop load calculations.

TECHNICAL SPECIFICATIONS	
SUPPLY VOLTAGE	20 V to 30 V DC
LOOP CURRENT - QUIESCENT	0.5 mA
LOOP CURRENT - SOUNDER/ BEACON ACTIVE	10 mA - 280 mW @ 28 V DC inc. isolator
MAXIMUM SOUNDER OUTPUT	108 dB (@ 1 meter - 30 V DC)
MAX. CABLE SIZE	2.5 mm <sup>2</sup>
OPERATING TEMPERATURE	-25°C to 70°C
MAX. HUMIDITY	95% RH Non-Condensing
CASE MATERIAL	ABS and PC
COLOUR	Red
PROTECTION CATEGORY	IP65 - Type B - Outdoor use
DIMENSIONS	112 (D) x 110 (H) mm inc. base
WEIGHT	315 g / 350 g - including packaging

ORDER CODE		
VALKYRIE ASI IP65	1328-CPR-0299	ADDRESSABLE WALL SOUNDER WITH ISOLATOR - IP65 RATED
VALKYRIE ASBI IP65	1328-CPR-0299	ADDRESSABLE WALL SOUNDER/ BEACON WITH ISOLATOR - IP65 RATED