

DS-PS1-I-WE(B) Wireless Internal Sounder



- 868 MHz two-way wireless communication
- Configurable arming/disarming prompt sound and LED indicator
- 3 years battery life span (triggered every two weeks and alerting 90 sec for each triggering)
- AES-128 encryption
- Front and rear panel tamper-proof
- 3 kinds of alarm sounds: fire alarm, panic alarm, and intrusion alarm
- Buzzer Decibel: 90 to 110 dB
- Fully remote configurable through APP
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission

▪ Specification

Electrical characteristics	
Operation humidity	10% to 90% (no condensing)
Operation temperature	-10 °C to 55 °C (14 °F to 131 °F)
Battery life span	Up to 3 years (standby time)
Wireless transmission	
RF frequency	868 MHz
RF modulation	2GFSK
RF distance	1.6 km (open area)
General	
Dimension(WxHxD)	88 mm × 88 mm × 32 mm (3.46" ×3.46" × 1.26")
Shell material	PC+ABS
Color	Blue/Red LED flash
Weight	169.5 g (6.0 oz)

▪ Available Model

DS-PS1-I-WE(B)

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq