

- • · DS-PWA96-M-WE x 1
- • · DS-PKF1-WE x 1
- • · DS-PK1-LT-WEx 1
- • · DS-PDP15P-EG2-WE x 2
- • · DS-PDMC-EG2-WE x 1
- • . DS-PS1-I-WE x 1



Specification

| Software features | | |
|--------------------------------|---|--|
| Diagnostics via the APP or Web | Supported | |
| Installer | 1 | |
| Installer APP for programming | Supported | |
| Onboard video clips | 4 | |
| Web server for maintenance | | |
| (offline configuration) | Supported | |
| Wi-Fi standard | Supported | |
| Arm modes | Away/Stay | |
| Firmware upgrade | APP/Web Portal | |
| Admin | 1 | |
| Wired network | Supported | |
| Programming tools | Hik-Connect/Hik-ProConnect/Web Portal/ IVMS4200/ Convergence Cloud | |
| Forced arming with open zones | Supported | |
| Memory log stored | 5000 | |
| User | 46 | |
| User APP for operating | Supported | |
| Voice prompt | Supported | |
| Area | 32 | |
| Automatic arm/disarm timers | Supported | |
| Hardware features | | |
| RS232 output | Supported | |
| SIM slot | Dual | |
| 3/4G on board | Supported | |
| Tag reader built in | Supported | |
| Loudspeaker built in | Supported | |
| Electrical characteristics | | |
| Battery type | Built in on board Battery Li | |
| Power supply | Built in power supply | |
| Operation temperature | -10 °C to +55 °C (The battery can not be charged at temperature lower than 10°C, | |
| | please make sure the adapter is connected) | |
| Battery life span | Up to 12 hours at normal temperature (The battery working time can be significantly | |
| battery life span | reduced at low temperatures) | |
| Wireless transmission | | |
| RF frequency | 868 Mhz | |
| RF method | Support | |
| Wireless security | Frequency Hoping 128 AES Encryption | |
| Display | | |
| LEDs status | Arm/Disarm, Alarm, Tamper, Fault, Cloud, Power | |
| General | | |
| Dimension(WxHxD) | 170.0 mm (6.7") × 170.0 (6.7") mm × 38.6 mm (1.5") | |
| Shell material | Plastic | |
| Color | White | |
| Weight | 557.5 g (19.7 oz) | |



| Device management | |
|-------------------|---|
| Tag | 48 |
| PIR cam | Supported |
| Zones | 96 (up to 48 PIRCAMs) |
| Keypad | 8 (including tag reader) |
| Wireless sounder | 6 (3 internal+3 external) |
| Wireless repeater | 4 |
| Keyfob | 48 |
| Multi Transmitter | 6 |
| Report method | |
| | SIA DC09 (SIA level 2, Contact ID), ISUP, ISAPI (SDK) |
| ARC protocol | Hik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) |
| | Supports video verification and remote control |

Available Model

DS-PWA96-Kit2-WE



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision Corporate Channel

