

Declaration of Conformity

This declaration of conformity is issued under the sole responsibility of the manufacturer.

We, ic audio GmbH, 68307 Mannheim, Boehringerstr. 14a, Germany

declare in exclusive responsibility that all ic audio products as listed in Appendix A

on that this declaration is based on, are compliant to the following norms or normative documents:

EMC Directive:

Directive 2014/30/EU of the European Parliament and of the Council of 26 February 2014 on the harmonisation of the laws of the Member States relating to electromagnetic compatibility

References to the relevant harmonized standards used or references to the specifications in relation to which conformity is declared:

DIN EN 55032 (VDE 0878-32):2022-08; EN 55032:2015+AC:2016+A11:2020+A1:2020

DIN EN 55035 (VDE 0878-35):2018-04; EN 55035:2017

DIN EN 55035/A11 (VDE 0878-35/A11):2022-06; EN 55035:2017/A11:2020

VDE Marks approval 96007, 21.12.2022



Mannheim, Germany 08.04.2025

A handwritten signature in blue ink, likely belonging to Linus Stimmel.

Linus Stimmel
Managing Director

Declaration of Conformity

Low Voltage Directive:

Directive 2014/35/EU of the European Parliament and of the Council of 26 February 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of electrical equipment designed for use within certain voltage limits

References to the relevant harmonized standards used or references to the specifications in relation to which conformity is declared:

EN 62368-1:2014
EN 62368-1:2014/+AC:2015

Products are compliant with European Parliament Directives 2002/95/EC (RoHS), 2011/65/EU (RoHS II) and 2015/863 (RoHS III)

Restriction of the use of certain hazardous substances in electrical and electronic equipment

References to the relevant harmonized standards used or references to the specifications in relation to which conformity is declared:

EN IEC 63000:2018

We hereby confirm that ic audio speakers do not use any RoHS restricted materials during the, manufacturing, storage or handling process. And to the best of our knowledge, the products offered in the ic audio pricelist do not contain any hazardous substances above the limits designated in the original RoHS Directive or any of its amendments. These substances namely comprise lead, cadmium, mercury, hexavalent chromium, polybrominated biphenyl (PBB) and polybrominated diphenyl ether (PBDE) flame retardants amendments.

Mannheim, Germany 08.04.2025

A handwritten signature in blue ink, appearing to read 'Stimmel'.

Linus Stimmel
Managing Director

Declaration of Conformity



CE compliance

Our products labeled with CE are compliant with European Parliament 2002/95/EC and 2011/65/EU.

EC Certificate of Conformity according to DIN EN 54-24:2008-06

Fire detection and fire alarm systems - Part 24:

Components of voice alarm systems - Loudspeakers



Declaration of Performance (DoP)

according to Construction Products Regulation (CPR) 305/2011

REACH compliance

Our products do not contain any substances

on the Candidate List of Substances of Very High Concern (SVHC),

according to the current listing published in accordance with Article 59(10) of the

REACH Regulation on the ECHA website (<https://echa.europa.eu/candidate-list-table>)

and referring to REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT

AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation,

Authorisation and Restriction of Chemicals (REACH).

Mannheim, Germany 08.04.2025

Linus Stimmel
Managing Director

Products list:

Art.No.	Type	Description
20122650	DA 10-260/T-EN54	Bi-directional speaker, 10 watts, RAL 9010, aluminium, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP65, 1438-CPR-1000
20102185	DA-S 20-130/T-EN54	Soundprojector, 20 watts, RAL 9010, aluminium, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP65, 1438-CPR-1000
20173235	DA-P 10-260/T-EN54	Bi-directional speaker, 10 watts, ABS, RAL9016, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP56, 1438-CPR-0388
20173441	DA-P 10-130/T-EN54	Soundprojector, 10 watts, ABS, white, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP56, 1438-CPR-0388
20142815	DA-P 20-130/T-EN54	Soundprojector, 20 watts, ABS, white, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP56, 1438-CPR-0388
20205823-PG	DK 10/T-EN54-PG	Horn speaker, 10 watts (100V & 20ohms), RAL 7035, ABS, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438-CPR-0242
20205824-PG	DK 15/T-EN54-PG	Horn speaker, 15 watts (100V & 20ohms), RAL 7035, ABS, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438-CPR-0242
20205825-PG	DK 30/T-EN54-PG	Horn speaker, 30 watts (100V & 20ohms), RAL 7035, ABS, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438-CPR-0242
20102232	DK-MH 30/T plus-EN54	Music horn, 2-way-system, 30 watts, RAL 7035, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438-CPR-0242
20194372	DL-P 10-165/T SWF-EN54	Ceiling speaker, seawater-resistant, 10 watts, RAL 9016, ABS, certified EN 54-24, IP54, 1438-CPR-0718
20102189	DL 06-130/T-EN54	Ceiling speaker, 6 watts, RAL 9010, metal, with thermal fuse and ceramic block, fireproof, certified EN 54-24, BS 5839 compliant, IP55, 1438-CPR-0233
20102191	DL 06-165/T-EN54	Ceiling speaker, 6 watts, RAL 9010, metal, with thermal fuse and ceramic block, fireproof, certified EN 54-24, BS 5839 compliant, IP55, 1438-CPR-0233
20206742	DL 06-165/T-EN54 STR	Ceiling speaker, 6 watts, RAL 9010, metal, with thermal fuse, ceramic block and strobe light, fireproof, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0233
20102182	DL-AB 06-200/T-EN54	Ceiling Speaker for AB-Cabling , 2x6 watts, RAL 9010, metal, with thermal fuse, ceramic block, fireproof, certified EN 54-24, BS 5839 compliant, IP55, 1438-CPR-0233
20142814	DL-FF 06-165/T-EN54	Ceiling speaker, 6 watts, RAL 9010, metal, with thermal fuse and ceramic block, fireproof, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0384
20132652	DL-E 06-130/T-EN54	Ceiling speaker, 6 watts, RAL 9016, metal, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0997
20132652S	DL-E 06-130/T-EN54 safe	Ceiling speaker, 6 watts, RAL 9016, metal, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0997
20132662	FE 130-EN54	Metal fire dome for DL-E 06-130/T-EN54, 1438-CPR-0997
20132653	DL-E 06-165/T-EN54	Ceiling speaker, 6 watts, RAL 9016, metal, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0997
20132653S	DL-E 06-165/T-EN54 safe	Ceiling speaker, 6 watts, RAL 9016, metal, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0997
20142907	DL-E 10-165/T-EN54 safe	Ceiling speaker, 10 watts, RAL 9016, metal, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0997
20132739	FE 165-EN54	Metal fire dome for DL-E 06-165/T-EN54, 1438-CPR-0997
20142905	DL-E-AB 06-100/T-EN54 safe	Ceiling Speaker for AB-Cabling , 2x6 watts, RAL 9016, metal, with thermal fuse, ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0997
20102195 SKD	DL-A 10-165/T-EN54 SKD	Ceiling speaker, surface-mounted version, 10 watts, RAL 9010, metal, with thermal fuse, ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPD/0232
20102196	DL-A 10-200/T-EN54	Ceiling speaker, surface-mounted version, 10 watts, RAL 9010, metal, with thermal fuse, ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPD/0232
20142910	DL-A-AB 06-100/T-EN54	Ceiling Speaker for AB-Cabling, surface-mounted version, 2x6 watts, RAL 9010, metal, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0448
20122605	DL-K 16-130/T-EN54	Sphere speaker, 16 watts, RAL 9010, ABS, with thermal fuse, ceramic block, certified EN 54-24, BS 5839 compliant, IP35, 1438/CPD/0325
20122601	TS-C 10-300/T-EN54	Sound column outdoor, incl. swivel bracket, 10 watts, RAL 9006, aluminium, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438/CPD/0315
20122602	TS-C 20-500/T-EN54	Sound column outdoor, incl. swivel bracket, 20 watts, RAL 9006, aluminium, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438/CPD/0315
20122603	TS-C 30-700/T-EN54	Sound column outdoor, incl. swivel bracket, 30 watts, RAL 9006, aluminium, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438/CPD/0315
20122604	TS-C 50-1000/T-EN54	Sound column outdoor, incl. swivel bracket, 50 watts, RAL 9006, aluminium, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438/CPD/0315
20194238	WA 06-77/T-EN54	Wall speaker, ABS, UL94V0, 6 watts, RAL 9016, with thermal fuse and ceramic block, certified EN 54-24, IP21C, 1438-CPR-0683

Art.No.	Type	Description
20102197	WA 06-165/T-EN54	Wall speaker, soft-line, 6 watts, MDF, white, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP54, 1438-CPR-0231
20102197V	WA 06-165/T-EN54V	Wall speaker, soft-line, 6 watts, MDF, white, with thermal fuse and ceramic block, ballproof, housing fixed by screws, certified EN 54-24, BS 5839 compliant, IP54, 1438-CPR-0231
20184119	WA 10-165/T-EN54	Wall speaker, soft-line, 10 watts, MDF, white, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP54, 1438-CPR-0231
20184119V	WA 10-165/T-EN54V	Wall speaker, soft-line, 10 watts, MDF, white, with thermal fuse and ceramic block, ballproof, housing fixed by screws, certified EN 54-24, BS 5839 compliant, IP54, 1438-CPR-0231
20102183	WA-AB 06-100/T-EN54	Wall Speaker for AB-Cabling, 2x6 watts, white, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP54, 1438/CPD/0230
20102183V	WA-AB 06-100/T-EN54V	Wall Speaker for AB-Cabling, 2x6 watts, white, with thermal fuse and ceramic block, ballproof, housing fixed by screws, certified EN 54-24, BS 5839 compliant, IP54, 1438/CPD/0230
20102198	WA 06-165/T Metal-EN54	Wall speaker, 6 watts, RAL 9010, metal, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0231
20184120	WA 10-165/T Metal-EN54	Wall speaker, 10 watts, RAL 9010, metal, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0231
20206749	WA 06-165/T Metal-EN54 STR	Wall speaker, 6 watts, RAL 9010, metal, with thermal fuse, ceramic block and strobe light, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0231
20102245	WU 06-165/T-EN54	Flush mounted speaker, 6 watts, ABS, white, with plastic housing, thermal fuse, ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0270
20142913	WU-AB 06-100/T-EN54	Flush mounted speaker for AB-Cabling, 2x6 watts, ABS, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0270
20102191-W	DL 06-165/T-EN54W	Ceiling speaker, 6 watts, RAL 9010, metal, with firedome, WAGO-connector 221, certified EN 54-24, IP55, 1438-CPR-0233
20102182-W	DL-AB 06-200/T-EN54W	Ceiling Speaker for AB-Cabling, 2x6 watts, RAL 9010, metal, with firedome, WAGO-connector 221, certified EN 54-24, IP55, 1438-CPR-0233
20132653-W	DL-E 06-165/T-EN54W	Ceiling speaker, 6 watts, RAL 9016, metal, WAGO-connector 221, certified EN 54-24, IP21C, 1438-CPR-0997
20102197-W	WA 06-165/T-EN54W	Wall speaker, soft-line, 6 watts, MDF, white, WAGO-connector 221, certified EN 54-24, IP54, 1438-CPR-0231
20102183-W	WA-AB 06-100/T-EN54W	Wall Speaker for AB-Cabling, 2x6 watts, white, WAGO-connector 221, certified EN 54-24, IP54, 1438-CPR-0230
20173441 - C	DA-P 10-130/T-EN54-C	Soundprojector, 10 watts, ABS, white, with thermal fuse and ceramic block, capacitor 2.2µF, 250V DC, certified EN 54-24, BS 5839 compliant, IP56, 1438-CPR-0388
20183521 - C	DA-P 20-130/T-EN54-C	Soundprojector, 20 watts, ABS, white, with thermal fuse and ceramic block, capacitor 4.7µF, 250V DC, certified EN 54-24, BS 5839 compliant, IP56, 1438-CPR-0388
20205823-PG-C	DK 10/T-EN54-PG-C	Horn speaker, 10 watts (100V & 20ohms), RAL 7035, ABS, with thermal fuse and ceramic block, capacitor 2.2µF, 250V DC, certified EN 54-24, BS 5839 compliant, IP66, 1438-CPR-0242
20205824-PG-C	DK 15/T-EN54-PG-C	Horn speaker, 15 watts (100V & 20ohms), RAL 7035, ABS, with thermal fuse and ceramic block, capacitor 2.2µF, 250V DC, certified EN 54-24, BS 5839 compliant, IP66, 1438-CPR-0242
20205825-PG-C	DK 30/T-EN54-PG-C	Horn speaker, 30 watts (100V & 20ohms), RAL 7035, ABS, with thermal fuse and ceramic block, capacitor 4.7µF, 250V DC, certified EN 54-24, BS 5839 compliant, IP66, 1438-CPR-0242
20183524 - C	DL-E 06-130/T-EN54-C	Ceiling speaker, 6 watts, RAL 9016, metal, capacitor 1µF, 250V DC, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0997
20183525 - C	DL-E 06-165/T-EN54-C	Ceiling speaker, 6 watts, RAL 9016, metal, capacitor 1µF, 250V DC, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0997
20173196-C	DL-SE 06-130/T-EN54-C	Ceiling speaker, 6 watts, RAL 9016, metal, with firedome and WAGO-connector 221, capacitor 2.2µF, 250V DC, certified EN 54-24, IP21C, 1438-CPR-0642
20173197-C	DL-SE 06-165/T-EN54-C	Ceiling speaker, 6 watts, RAL 9016, metal, with firedome and WAGO-connector 221, capacitor 2.2µF, 250V DC, certified EN 54-24, IP21C, 1438-CPR-0642
20194234-C	DL-SE 10-200/T-EN54-C	Ceiling speaker, 6 watts, RAL 9016, metal, with firedome and WAGO-connector 221, capacitor 2.2µF, 250V DC, certified EN 54-24, IP21C, 1438-CPR-0642
20102197 - C	WA 06-165/T-EN54-C	Wall speaker, soft-line, 6 watts, MDF, white, with thermal fuse and ceramic block, capacitor 1µF, 250V DC, certified EN 54-24, BS 5839 compliant, IP54, 1438-CPR-0231
20102198 - C	WA 06-165/T Metall-EN54-C	Wall speaker, 6 watts, RAL 9010, metal, with thermal fuse and ceramic block, capacitor 1µF, 250V DC, certified EN 54-24, BS 5839 compliant, IP21C, 1438-CPR-0231
20227870	WA-S 06-100/T EN54	Wall speaker, slim-line, 6 watts, ABS, white, with WAGO-connector 221, certified EN 54-24, IP21, 1438-CPR-0984
20238096	WA-S 06-165/T-EN54	Wall speaker, slim-line, 6 watts, ABS, white, with WAGO-connector 221, certified EN 54-24, IP21, 1438-CPR-0984
20205425	DA-D 20-130/T-EN54	Soundprojector, 20 watts, RAL 9016, ABS, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP65, 1438-CPR-0758
20238082	DL-SE 06-66/T-EN54	Ceiling speaker, 6 watts, RAL 9016, metal, with firedome and WAGO-connector 221, certified EN 54-24, IP21C, 0068-CPR-208/2024
20206395	DL-SE 06-100/T-EN54	Ceiling speaker, 6 watts, RAL 9016, metal, with firedome and WAGO-connector 221, certified EN 54-24, IP54, 1438-CPR-0642
20173196	DL-SE 06-130/T-EN54	Ceiling speaker, 6 watts, RAL 9016, metal, with firedome and WAGO-connector 221, certified EN 54-24, IP21C, 1438-CPR-0642

Art.No.	Type	Description
20173325	DL-SQ 06-130/T-EN54	Square design ceiling speaker, 6 watts, RAL 9016, metal, with fireproof and WAGO-connector 221, certified EN 54-24, IP21C, 1438-CPR-0642
20173197	DL-SE 06-165/T-EN54	Ceiling speaker, 6 watts, RAL 9016, metal, with fireproof and WAGO-connector 221, certified EN 54-24, IP21C, 1438-CPR-0642
20194233	DL-SE 10-165/T-EN54	Ceiling speaker, 10 watts, RAL 9016, metal, with fireproof and WAGO-connector 221, certified EN 54-24, IP21C, 1438-CPR-0642
20194236	DL-SE 10-165/T plus-EN54	Plastic ceiling speaker with steel grille and fireproof, 10 watts, RAL 9016 certified EN 54-24, IP21C, 1438-CPR-0642
20194234	DL-SE 10-200/T-EN54	Ceiling speaker, 10 watts, RAL 9016, metal, with fireproof and WAGO-connector 221, certified EN 54-24, IP21C, 1438-CPR-0642
20194235	DL-SE 20-200/T-EN54	Ceiling speaker, 20 watts, RAL 9016, metal, with fireproof and WAGO-connector 221, certified EN 54-24, IP21C, 1438-CPR-0642
20227846	DL-SE 20-200/T plus-EN54	Plastic ceiling speaker with steel grille and fireproof, 20 watts, RAL 9016 certified EN 54-24, IP21C, 1438-CPR-0642
20248555	DL-SE-AB 06-200/T-EN54	Ceiling Speaker for AB-Cabling, 2x6 watts, RAL 9016, metal, with fireproof and WAGO-connector 221, certified EN 54-24, IP21C, 1438-CPR-0642
20205426	DL-H 20-100/T plus white-EN54	Hemi-sphere speaker, 2-way-system, bassreflex, 20 watts (100V & 8ohms), RAL 9016, ABS, with thermal fuse, ceramic block, certified EN 54-24, BS 5839 compliant, IP65, 1438-CPR-0766
20238240	DL-H 20-100/T plus black-EN54	Hemi-sphere speaker, 2-way-system, bassreflex, 20 watts (100V & 8ohms), black, ABS, with thermal fuse, ceramic block, certified EN 54-24, BS 5839 compliant, IP65, 1438-CPR-0766
20238101	DL-H 60-165/T plus white-EN54	Hemi-sphere speaker, 2-way-system, bassreflex, 60 watts (100V & 8ohms), RAL 9016, ABS, thermal fuse, ceramic block, certified EN 54-24, BS 5839 compliant, IP65, 1438-CPR-0766
20238241	DL-H 60-165/T plus black-EN54	Hemi-sphere speaker, 2-way-system, bassreflex, 60 watts (100V & 8ohms), black, ABS, thermal fuse, ceramic block, certified EN 54-24, BS 5839 compliant, IP65, 1438-CPR-0766
20238242	DL-S 15-100/T plus-EN54	Bassreflex-ceiling speaker, 2-way-system, 15 watts (100V & 8ohms), RAL 9016, fireproof certified EN 54-24, IP21C, 1438-CPR-xxxx
20238243	DL-S 30-130/T plus-EN54	Bassreflex-ceiling speaker, 2-way-system, 30 watts (100V & 8ohms), RAL 9016, fireproof certified EN 54-24, IP21C, 1438-CPR-xxxx
20194132	DL-S 50-165/T plus-EN54	Ceiling speaker, 2-way-system, 50 watts (100V & 8ohms), RAL 9016, metal, fireproof certified EN 54-24, IP21C, 1438-CPR-0431
20238059	DA-SG 80-200/T plus white-EN54	Bassreflex-garden speaker, 2-way-system, 80 watts (100V & 8ohm), ABS, white certified EN 54-24, IP66, 1438-CPR-xxxx
20248438	DA-SG 80-200/T plus green-EN54	Bassreflex-garden speaker, 2-way-system, 80 watts (100V & 8ohm), ABS, green certified EN 54-24, IP66, 1438-CPR-xxxx
20122643	MS 15-100/T white-EN54	Monitor speaker, 2-way-system, swivel bracket included, 15 watts (100V & 8ohms), ABS, white, certified EN54-24, BS 5839 compliant, 1438-CPR-0998
20122644	MS 15-100/T black-EN54	Monitor speaker, 2-way-system, swivel bracket included, 15 watts (100V & 8ohms), ABS, black, certified EN54-24, BS 5839 compliant, 1438-CPR-0998
20122645	MS 30-130/T white-EN54	Monitor speaker, 2-way-system, swivel bracket included, 30 watts (100V & 8ohms), ABS, white, certified EN54-24, BS 5839 compliant, 1438-CPR-0998
20122646	MS 30-130/T black-EN54	Monitor speaker, 2-way-system, swivel bracket included, 30 watts (100V & 8ohms), ABS, black, certified EN54-24, BS 5839 compliant, 1438-CPR-0998
20122647	MS 50-165/T white-EN54	Monitor speaker, 2-way-system, swivel bracket included, 50 watts (100V & 8ohms), ABS, white, certified EN54-24, BS 5839 compliant, 1438-CPR-0998
20122648	MS 50-165/T black-EN54	Monitor speaker, 2-way-system, swivel bracket included, 50 watts (100V & 8ohms), ABS, black, certified EN54-24, BS 5839 compliant, 1438-CPR-0998
20206427	PRO 150-200/T plus white-EN54	Coaxial horn speaker, 2-way-system, bassreflex, 150 watts, white, ABS, certified EN 54-24, IP66, 1438-CPR-0814
20217063	PRO 150-200/T plus black-EN54	Coaxial horn speaker, 2-way-system, bassreflex, 150 watts, white, ABS, certified EN 54-24, IP66, 1438-CPR-0814
20206428	PRO 250-300/T plus white-EN54	Coaxial horn speaker, 2-way-system, bassreflex, 250 watts, white, ABS, certified EN 54-24, IP66, 1438-CPR-0814
20217067	PRO 250-300/T plus black-EN54	Coaxial horn speaker, 2-way-system, bassreflex, 250 watts, white, ABS, certified EN 54-24, IP66, 1438-CPR-0814
20206683	DS 100/T plus white-EN54	High performance 2-way Array Speaker, 100 watts, RAL 9016, certified EN 54-24, IP21C, 1438-CPR-0983
20217322	DS 100/T plus white-EN54 Line Array	4 pcs Array Kit: High performance 2-way Array Speaker, 100 watts, RAL 9016, certified EN 54-24, IP21C, 1438-CPR-0983
20205416	TH 100 - EN54 black V20	Boundary horn speaker for Voice Alarm, 100W, black, ABS, certified EN 54-24, BS 5839 compliant, IP66, 1438-CPR-0481
20163071	TH-100-WH-V5A	TH-100 mounting brackets for Voice Alarm, 4 pieces, made of stainless steel (1.4571, AISI 316), 1438-CPR-0481
20163069	TH-100-PH-V5A	TH-100 premium mounting kit for Voice Alarm, made of stainless steel (1.4571, AISI 316), 1438-CPR-0481
20248539	WA 06-77/T CLR	Wall speaker, ABS, UL94V0, 6 watts, RAL 9016, for clean room application ISO 14644-1, class 1.
20248560	DL-D 30-130 Dante	Bassreflex ceiling speaker, active powered 2-way-system, 30 watts, RAL 9016, fireproof, integrated Dante® interface for network audio
20248566	MS-D 30-165 white Dante	Bassreflex monitor speaker, active powered 2-way-system, swivel bracket included, 30 watts, ABS, white, integrated Dante® interface for network audio
20248561	MS-D 30-165 black Dante	Bassreflex monitor speaker, active powered 2-way-system, swivel bracket included, 30 watts, ABS, black, integrated Dante® interface for network audio
20248628	TS-D 320-1000 white Dante	Active, steerable line-array system, 320W, 8-channel Class-D digital amplifier, 8 x 100mm high performance speaker, DSP, software, integrated Dante® interface for network audio